

SITE LITE FUTURE LED BASIC 2600LM 850 230V IP44 I KL. 3M WT.UNI-SCHUKO Z GNIAZDEM SCHUCKO SZARY (23W) Z MAGNESAMI

DETAILED CARD



TECHNICAL PARAMETERS

Index:	621338
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	23
Colour temperature [K]:	5000
Luminous flux [lm]*:	2600
Electrical protection class:	I
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	milky

CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

Available versions:

- with sockets: PL-FR, DK, SCHUCKO
- without sockets:
- with a magnet in the base

APPLICATION

The luminaire will provide precise illumination of the workplace. It can be used as a workplace luminaire to illuminate workplaces and construction sites. The smaller size and compact design make it more convenient to transport. The luminaire is designed for outdoor use, industrial applications or other applications where the lighting standards allow CRI <80.

SITE LITE FUTURE LED BASIC 2600LM 850 230V IP44 I KL. 3M WT.UNI-SCHUKO Z GNIAZDEM SCHUCKO SZARY (23W) Z MAGNESAMI

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	621338	Ingress protection:	IP54
Category type:	general construction site lighting	Plug type:	UNI-SCHUKO
Light source:	LED module	Socket type:	SCHUKO
Nominal power [W]:	23	Sockets:	1
Luminous flux [lm]:	2600	Cable length [m]:	3
Supply voltage [V]:	220-240	Magnet:	yes
Electrical protection class:	I	Net weight [kg]:	1.300
Colour temperature [K]:	5000	Dimensions (H/W/T/S) [mm]:	ø198/154
Diffuser material:	PC	Manual:	Download PDF
Diffuser type:	milky	Luminous efficacy [lm/W]:	133
Material of the body:	PP	Energy efficiency class:	E
Colour of the body:	graphite	Warranty [years]:	3
Impact resistance:	IK10	CE certificate:	270/2023