SITE LITE FUTURE LED BASIC 2600LM 850 230V IP54 II KL. 3M WT.UNI-SCHUKO SZARY (23W) Z MAGNESAMI

DETAILED CARD



TECHNICAL PARAMETERS

Index:	621321
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	23
Colour temperature [K]:	5000
Luminous flux [lm]*:	2600
Electrical protection class:	II
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	milky

CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging and a cable winder in the housing.

The variety of available versions ensures optimal adjustment to your needs.

Available versions:

• with sockets: PL-FR, DK, SCHUCKO

• without sockets:

• with a magnet in the base

APPLICATION

The luminaire will provide precise illumination of the workplace. It can be used as a workplace luminaire to illuminate workplaces and construction sites. The smaller size and compact design make it more convenient to transport. The luminaire is designed for outdoor use, industrial applications or other applications where the lighting standards allow CRI <80.

SITE LITE FUTURE LED BASIC 2600LM 850 230V IP54 II KL. 3M WT.UNI-SCHUKO SZARY (23W) Z MAGNESAMI

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	621321	**Impact resistance:**	IK10
Category type:	general construction site lighting	**Ingress protection:**	IP54
Light source:	LED module	**Plug type:**	UNI-SCHUKO
Nominal power [W]:	23	**Cable length [m]:**	3
Luminous flux [lm]:	2600	**Magnet:**	yes
Supply voltage [V]:	220-240	**Net weight [kg]:**	1.300
Electrical protection class:	II	**Dimensions (H/W/T/S) [mm]:**	ø198/154
Colour temperature [K]:	5000	**Manual:**	Download PDF
Diffuser material:	PC	**Luminous efficacy [lm/W]:**	133
Diffuser type:	milky	**Energy efficiency class:**	E
Material of the body:	PP	**Warranty [years]:**	3
Colour of the body:	graphite	**CE certificate:**	270/2023

Card creation date: 23 September 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 270/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl