

FUTURE LINE LED 11.5M 4X680LM II KL. SZARY 850 (4X8W) Z MAGNESAMI

DETAILED CARD



TECHNICAL PARAMETERS

Index:	248559
Ingress protection:	IP44
Impact resistance:	IK09
Nominal power [W]:	32
Colour temperature [K]:	5000
Luminous flux [lm]*:	2720
Electrical protection class:	II
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	milky

CHARACTERISTICS

FUTURE LINE LED is a rope light for quick and temporary lighting of the workplace. Available in versions with 3 and 4 luminaires on one rope, it allows to connect them to a maximum of 40 lighting points (10 separate chains). The special shape of luminaires allows for their assembly in construction site conditions (on nails, screws, pipes, scaffolding, etc.) and further free positioning of the light beam. The ropes are equipped with hooks for fixing the cable, multi-purpose mounting brackets and magnets screwed into various places of the luminaire. The length of one lighting chain is 11.5 m (version with 4 luminaires) or 9 m (version with 3 luminaires). Possibility of creating max. 115 m of light line (10x Future Line LED 4x8W luminaire).

Comes as standard: rubber cable H07RN-F 2x1 mm, 23 m initial cable with a plug, 2.5 m between luminaires, 1 m end cable with a socket.

Multi-purpose mounting bracket included.

APPLICATION

An innovative lighting chain designed for fast and universal lighting of workplaces. Its unique shape and functional design allow for express assembly even in non-typical places.

FUTURE LINE LED 11.5M 4X680LM II KL. SZARY 850 (4X8W) Z MAGNESAMI

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	248559	Impact resistance:	IK09
Category type:	general construction site lighting	Ingress protection:	IP44
Light source:	LED module	Version:	4x1
Nominal power [W]:	32	Plug type:	standard 2-PIN
Luminous flux [lm]:	2720	Socket type:	standard 2-PIN
Supply voltage [V]:	220-240	Sockets:	1
Electrical protection class:	II	Cable length [m]:	11
Colour temperature [K]:	5000	Magnet:	yes
Diffuser material:	PC	Net weight [kg]:	0.300
Diffuser type:	milky	Energy efficiency class:	A
Material of the body:	PP	Luminous efficacy [lm/W]:	400
Colour of the body:	grey	CE certificate:	268/2023
Dimensions (H/W/T/S) [mm]:	141/109/67	Manual:	Download PDF

Card creation date: 30 June 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 268/2023