

FUTURE LINE LED 48V 9M 3X1000LM III KL. SZARY 850 (3X10W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	246937
Ingress protection:	IP20
Impact resistance:	IK08
Nominal power [W]:	34
Colour temperature [K]:	5000
Luminous flux [lm]*:	3000
Energy efficiency class:	D
Electrical protection class:	III
Material of the body:	PP
Diffuser material:	PC

CHARACTERISTICS

FUTURE LINE LED is a rope light for quick and temporary lighting of the workplace. Available in versions with 3 and 4 luminaires on one rope, it allows to connect them to a maximum of 40 lighting points (10 separate chains). The special shape of luminaires allows for their assembly in construction site conditions (on nails, screws, pipes, scaffolding, etc.) and further free positioning of the light beam. The ropes are equipped with hooks for fixing the cable, multi-purpose mounting brackets and magnets screwed into various places of the luminaire. The length of one lighting chain is 11.5 m (version with 4 luminaires) or 9 m (version with 3 luminaires). Possibility of creating max. 115 m of light line (10x Future Line LED 4x8W luminaire).

Comes as standard: rubber cable H07RN-F 2x1 mm, 23 m initial cable with a plug, 2.5 m between luminaires, 1 m end cable with a socket.

Multi-purpose mounting bracket included.

APPLICATION

An innovative lighting chain designed for fast and universal lighting of workplaces. Its unique shape and functional design allow for express assembly even in non-typical places.

FUTURE LINE LED 48V 9M 3X1000LM III KL. SZARY 850 (3X10W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	34	Colour of the body:	grey
Index:	246937	Impact resistance:	IK08
Colour temperature [K]:	5000	Ingress protection:	IP20
EAN:	5905963246937	Version:	3x1
Luminous flux [lm]:	3000	Cable length [m]:	9
Category type:	general construction site lighting	Hook:	1
Light source:	LED module	Dimensions of single box [mm]:	395/148/195
Supply voltage [V]:	42 - 48	Dimensions of bulk box (H/W/D) [mm]:	1190/790/980
Luminous efficacy [lm/W]:	119	Number in carton box [pcs]:	75
Energy efficiency class:	D	Accessories included:	Hook, universal mounting band
Electrical protection class:	III	Manual:	Download PDF
Diffuser material:	PC		
Material of the body:	PP		

Card creation date: 30 June 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 269/2023