FUTURE LINE LED 48V 9M 3X1000LM III KL. SZARY 850 (3X10W) Z MAGNESAMI

DETAILED CARD



TECHNICAL PARAMETERS

Index:	246944
Ingress protection:	IP20
Impact resistance:	IK08
Nominal power [W]:	34
Colour temperature [K]:	5000
Luminous flux [lm]*:	3000
Energy efficiency class:	D
Electrical protection class:	III
Material of the body:	PP
Diffuser material:	PC

CHARACTERISTICS

FUTURE LINE LED is a rope light for quick and temporary lighting of the workplace. Available in versions with 3 and 4 luminaires on one rope, it allows to connect them to a maximum of 40 lighting points (10 separate chains). The special shape of luminaires allows for their assembly in construction site conditions (on nails, screws, pipes, scaffolding, etc.) and further free positioning of the light beam. The ropes are equipped with hooks for fixing the cable, multi-purpose mounting brackets and magnets screwed into various places of the luminaire. The length of one lighting chain is 11.5 m (version with 4 luminaires) or 9 m (version with 3 luminaires). Possibility of creating max. 115 m of light line (10x Future Line LED 4x8W luminaire).
Comes as standard: rubber cable H07RN-F 2x1 mm, 23 m initial cable with a plug, 2.5 m between luminaires, 1 m end cable with a socket.
Multi-purpose mounting bracket included.

APPLICATION

An innovative lighting chain designed for fast and universal lighting of workplaces. Its unique shape and functional design allow for express assembly even in non-typical places.

FUTURE LINE LED 48V 9M 3X1000LM III KL. SZARY 850 (3X10W) Z MAGNESAMI

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	246944
EAN:	5905963246944
Category type:	general construction site lighting
Light source:	LED module
Nominal power [W]:	34
Luminous flux [lm]:	3000
Supply voltage [V]:	42 - 48
Luminous efficacy [lm/W]:	119
Energy efficiency class:	D
Electrical protection class:	III
Colour temperature [K]:	5000
Diffuser material:	PC
Material of the body:	PP

Colour of the body:	grey
Impact resistance:	IK08
Ingress protection:	IP20
Version:	3x1
Cable length [m]:	9
Hook:	yes
Magnet:	yes
Dimensions of single box [mm]:	395/148/195
Dimensions of bulk box (H/W/D) [mm]:	1190/790/980
Number in carton box [pcs]:	75
Accessories included:	Hook, universal mounting band
Manual:	Download PDF

Card creation date: 30 June 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 269/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl