
MAGNUM FUTURE 1600LM 120ST UNI-SCHUKO

DETAILED CARD



TECHNICAL PARAMETERS

Index:	256943
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	20
Supply voltage [V]:	220-240
Luminous flux [lm]*:	1600
Electrical protection class:	II
Colour temperature [K]:	4000
Beam angle [°]:	120
Diffuser material:	PC

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Made of impact-resistant polipropylen (PP). Anti-glare diffuser which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. The smaller size and compact design make it convenient to transport. It is equipped with a movable, multi-position arm also acting as a hook. Multi-purpose mounting bracket included.
It can be mounted on a Future Stand, significantly increasing the range and comfort of use.

APPLICATION

It can be used as a workplace luminaire to illuminate workplaces and construction sites. The smaller size and compact design make it more convenient to transport. The luminaire is designed for outdoor use, industrial applications or other applications where the lighting standards allow CRI <80.

MAGNUM FUTURE 1600LM 120ST UNI-SCHUKO

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	20
Supply voltage [V]:	220-240
Luminous flux [lm]:	1600
Electrical protection class:	II
Colour temperature [K]:	4000
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	frozen
Material of the body:	PP
Colour of the body:	grey
Impact resistance:	IK10

Ingress protection:	IP54
Plug type:	UNI-SCHUKO
Cable length [m]:	3
Net weight [kg]:	0.900
Index:	256943
Category type:	workplace floodlights
Dimensions (H/W/T/S) [mm]:	192/193/123
Manual:	Download PDF
Warranty [years]:	3
ETIM class:	EC000347
Energy efficiency class:	F
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018

MAGNUM FUTURE 1600LM 120ST UNI-SCHUKO


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 134/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl