MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI CH

DETAILED CARD



TECHNICAL PARAMETERS

Index:	247033
Ingress protection:	IP55
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Supply voltage [V]:	220-240
Luminous flux [lm]*:	4300
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.
A rubber cable H07RN-F 3x1.5 mm2 (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI CH

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	247033	**Dimensions (H/W/T/S) [mm]:**	300/400/100
Light source:	LED module	**Impact resistance:**	IK10
Nominal power [W]:	32	**Ingress protection:**	IP55
Rated power of the luminaire [W]:	32	**Plug type:**	CH
Supply voltage [V]:	220-240	**Socket type:**	CH
Luminous flux [lm]:	4300	**Sockets:**	2
Energy efficiency class:	D	**Cable length [m]:**	5
Electrical protection class:	I	**Net weight [kg]:**	2.800
Colour temperature [K]:	4000	**Category type:**	workplace floodlights
Beam angle [°]:	120	**ETIM class:**	EC000347
Diffuser material:	PC	**Technical Warranty:**	5
Diffuser type:	frozen	**CE certificate:**	175/2023
Material of the body:	PP	**Manual:**	Download PDF
Colour of the body:	grey		

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI CH


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 18 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 175/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl