

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI CH BACKLIGHT

DETAILED CARD



TECHNICAL PARAMETERS

Index:	247118
Ingress protection:	IP44
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Supply voltage [V]:	220-240
Luminous flux [lm]*:	4300
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm2 (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI CH BACKLIGHT

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Impact resistance:	IK10
Nominal power [W]:	32	Ingress protection:	IP44
Supply voltage [V]:	220-240	Plug type:	CH
Luminous flux [lm]:	4300	Socket type:	CH
Energy efficiency class:	D	Sockets:	2
Electrical protection class:	I	Cable length [m]:	5
Colour temperature [K]:	4000	Switch:	yes
Beam angle [°]:	120	Net weight [kg]:	3
Diffuser material:	PC	Index:	247118
Diffuser type:	frozen	Category type:	workplace floodlights
Material of the body:	PP	Version:	BACKLIGHT
Colour of the body:	grey	ETIM class:	EC000347
Dimensions (H/W/T/S) [mm]:	300/400/100	Manual:	Download PDF

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI CH BACKLIGHT

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date:13 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 175/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl