# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI CH WYŁĄCZNIK

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Index:** | 247071 |
| **Ingress protection:** | IP44 |
| **Impact resistance:** | IK10 |
| **Rated power of the luminaire [W]*:** | 32 |
| **Supply voltage [V]:** | 220-240 |
| **Luminous flux [lm]*:** | 4300 |
| **Energy efficiency class:** | D |
| **Electrical protection class:** | I |
| **Colour temperature [K]:** | 4000 |

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.
A rubber cable H07RN-F 3x1.5 mm2 (3 m) comes as standard.

## APPLICATION

The luminaire will provide precise illumination of the workplace.

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI CH WYŁĄCZNIK

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | | | |
|---|---|---|---|
| **Index:** | 247071 | **Dimensions (H/W/T/S) [mm]:** | 300/400/100 |
| **Light source:** | LED module | **Impact resistance:** | IK10 |
| **Nominal power [W]:** | 32 | **Ingress protection:** | IP44 |
| **Rated power of the luminaire [W]:** | 32 | **Plug type:** | CH |
| **Supply voltage [V]:** | 220-240 | **Socket type:** | CH |
| **Luminous flux [lm]:** | 4300 | **Sockets:** | 2 |
| **Energy efficiency class:** | D | **Cable length [m]:** | 5 |
| **Electrical protection class:** | I | **Switch:** | yes |
| **Colour temperature [K]:** | 4000 | **Net weight [kg]:** | 2.900 |
| **Beam angle [°]:** | 120 | **Category type:** | workplace floodlights |
| **Diffuser material:** | PC | **ETIM class:** | EC000347 |
| **Diffuser type:** | frozen | **Technical Warranty:** | 5 |
| **Material of the body:** | PP | **CE certificate:** | 175/2023 |
| **Colour of the body:** | grey | **Manual:** | Download PDF |

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI CH WYŁĄCZNIK


DETAILED CARD

## ACCESSORIES AVAILABLE

| index | Name |
|---|---|
| 000737 | FUTURE STAND Tripod with Click Head System |
| 000720 | Standard tripod |



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)



The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 175/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl