

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI DK

DETAILED CARD



## TECHNICAL PARAMETERS

|   |         |
|---|---------|
| <b>Index:</b>                             | 247026  |
| <b>Ingress protection:</b>                | IP44    |
| <b>Impact resistance:</b>                 | IK10    |
| <b>Rated power of the luminaire [W]*:</b> | 32      |
| <b>Supply voltage [V]:</b>                | 220-240 |
| <b>Luminous flux [lm]*:</b>               | 4300    |
| <b>Energy efficiency class:</b>           | D       |
| <b>Electrical protection class:</b>       | I       |
| <b>Colour temperature [K]:</b>            | 4000    |

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm<sup>2</sup> (3 m) comes as standard.

## APPLICATION

The luminaire will provide precise illumination of the workplace.

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI DK

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |            |                              |                              |
|-----------------------------------|------------|------------------------------|------------------------------|
| Index:                            | 247026     | Electrical protection class: | I                            |
| Nominal power [W]:                | 32         | Ingress protection:          | IP44                         |
| Colour temperature [K]:           | 4000       | Beam angle [°]:              | 120                          |
| Light source:                     | LED module | Diffuser material:           | PC                           |
| Luminous flux [lm]:               | 4300       | Diffuser type:               | frozen                       |
| Rated power of the luminaire [W]: | 32         | Material of the body:        | PP                           |
| Plug type:                        | DK         | Colour of the body:          | grey                         |
| Supply voltage [V]:               | 220-240    | Dimensions (H/W/T/S) [mm]:   | 300/400/100                  |
| Socket type:                      | DK         | Impact resistance:           | IK10                         |
| Sockets:                          | 2          | Net weight [kg]:             | 2.800                        |
| Cable length [m]:                 | 5          | Category type:               | workplace floodlights        |
| Energy efficiency class:          | D          | ETIM class:                  | EC000347                     |
|                                   |            | Technical Warranty:          | 5                            |
|                                   |            | CE certificate:              | <a href="#">175/2023</a>     |
|                                   |            | Manual:                      | <a href="#">Download PDF</a> |

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI DK

DETAILED CARD

## ACCESSORIES AVAILABLE

| index  | Name                                       |
|--------|--|
| 000737 | FUTURE STAND Tripod with Click Head System |
| 000720 | Standard tripod                            |



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 18 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 175/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl