

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI DK WYŁĄCZNIK

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	247064
<b>Ingress protection:</b>	IP44
<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]*:</b>	32
<b>Supply voltage [V]:</b>	220-240
<b>Luminous flux [lm]*:</b>	4300
<b>Energy efficiency class:</b>	D
<b>Electrical protection class:</b>	I
<b>Colour temperature [K]:</b>	4000

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm<sup>2</sup> (3 m) comes as standard.

## APPLICATION

The luminaire will provide precise illumination of the workplace.

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI DK WYŁĄCZNIK

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	247064	Electrical protection class:	I
Nominal power [W]:	32	Ingress protection:	IP44
Colour temperature [K]:	4000	Beam angle [°]:	120
Light source:	LED module	Diffuser material:	PC
Luminous flux [lm]:	4300	Diffuser type:	frozen
Rated power of the luminaire [W]:	32	Material of the body:	PP
Plug type:	DK	Colour of the body:	grey
Supply voltage [V]:	220-240	Dimensions (H/W/T/S) [mm]:	300/400/100
Socket type:	DK	Impact resistance:	IK10
Sockets:	2	Net weight [kg]:	2.900
Cable length [m]:	5	Category type:	workplace floodlights
Switch:	yes	ETIM class:	EC000347
Energy efficiency class:	D	Technical Warranty:	5
		CE certificate:	<a href="#">175/2023</a>
		Manual:	<a href="#">Download PDF</a>

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI DK WYŁĄCZNIK

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 18 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 175/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl