

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI DK WYŁĄCZNIK

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|---------|
| Index: | 247064 |
| Ingress protection: | IP44 |
| Impact resistance: | IK10 |
| Rated power of the luminaire [W]*: | 32 |
| Supply voltage [V]: | 220-240 |
| Luminous flux [lm]*: | 4300 |
| Energy efficiency class: | D |
| Electrical protection class: | I |
| Colour temperature [K]: | 4000 |

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm² (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI DK WYŁĄCZNIK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|------------------------------|------------------------------|
| Index: | 247064 | Electrical protection class: | I |
| Nominal power [W]: | 32 | Ingress protection: | IP44 |
| Colour temperature [K]: | 4000 | Beam angle [°]: | 120 |
| Light source: | LED module | Diffuser material: | PC |
| Luminous flux [lm]: | 4300 | Diffuser type: | frozen |
| Rated power of the luminaire [W]: | 32 | Material of the body: | PP |
| Plug type: | DK | Colour of the body: | grey |
| Supply voltage [V]: | 220-240 | Dimensions (H/W/T/S) [mm]: | 300/400/100 |
| Socket type: | DK | Impact resistance: | IK10 |
| Sockets: | 2 | Net weight [kg]: | 2.900 |
| Cable length [m]: | 5 | Category type: | workplace floodlights |
| Switch: | yes | ETIM class: | EC000347 |
| Energy efficiency class: | D | Technical Warranty: | 5 |
| | | CE certificate: | 175/2023 |
| | | Manual: | Download PDF |

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI DK WYŁĄCZNIK

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|--|
| 000737 | FUTURE STAND Tripod with Click Head System |
| 000720 | Standard tripod |



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 18 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 175/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl