

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI PL-FR BACKLIGHT

DETAILED CARD



TECHNICAL PARAMETERS

Index:	x
Ingress protection:	IP44; IP54; IP55
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Supply voltage [V]:	12; 24; 220-240; 42-48; 110
Frequency [Hz]:	50-60
Luminous flux [lm]*:	2900; 3100; 3300; 4300
Energy efficiency class:	D; E; F
Electrical protection class:	I; II; III
Colour temperature [K]:	4000

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm2 (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI PL-FR BACKLIGHT

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	moduł LED	Impact resistance:	IK10
Nominal power [W]:	32	Ingress protection:	IP44; IP54; IP55
Supply voltage [V]:	12; 24; 220-240; 42-48; 110	Plug type:	CEE; CH; DK; TRAFO; UNI-SCHUKO
Frequency [Hz]:	50-60	Socket type:	max SCHUKO
Luminous flux [lm]:	2900; 3100; 3300; 4300	Sockets:	2
Energy efficiency class:	D; E; F	Wire type:	H07RN-F 2x1,0mm; H07RN-F 2x1mm; H07RN-F 3x1,5mm
Electrical protection class:	I; II; III	Cable length [m]:	5
Colour temperature [K]:	4000	Switch:	yes
Colour rendering index:	>80	Net weight [kg]:	2.600; 2.800; 2.900; 3.000
SDCM:	≤ 3	Index:	x
Beam angle [°]:	120	EAN:	x
Diffuser material:	PC	Category type:	workplace floodlights
Diffuser type:	mrożony	Version:	BACKLIGHT
Diffuser colour:	biały	LED lifespan L70B50 [h]:	50000
Material of the body:	100% recycled plastic; PP	ETIM class:	EC000346; EC000347
Colour of the body:	czarny; szary	Photobiological safety:	grupa ryzyka 1 (niskie ryzyko)
Dimensions (H/W/T/S) [mm]:	300/400/100	Manual:	Download PDF

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI PL-FR BACKLIGHT

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date:13 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 175/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl