

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI PL-FR PRZESŁ.TORÓW PRĄDOWYCH

DETAILED CARD



TECHNICAL PARAMETERS

Index:	247309
Ingress protection:	IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Supply voltage [V]:	220-240
Luminous flux [lm]*:	4300
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm² (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI PL-FR PRZESŁ.TORÓW PRĄDOWYCH

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	247309	Dimensions (H/W/T/S) [mm]:	300/400/100
Light source:	LED module	Impact resistance:	IK10
Nominal power [W]:	32	Ingress protection:	IP54
Rated power of the luminaire [W]:	32	Plug type:	UNI-SCHUKO
Supply voltage [V]:	220-240	Socket type:	PL-FR
Luminous flux [lm]:	4300	Sockets:	2
Energy efficiency class:	D	Cable length [m]:	5
Electrical protection class:	I	Net weight [kg]:	2.800
Colour temperature [K]:	4000	Category type:	workplace floodlights
Beam angle [°]:	120	ETIM class:	EC000347
Diffuser material:	PC	Technical Warranty:	5
Diffuser type:	frozen	CE certificate:	175/2023
Material of the body:	PP	Manual:	Download PDF
Colour of the body:	grey		

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI PL-FR PRZESŁ.TORÓW PRĄDOWYCH

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 18 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 175/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl