

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI SCHUKO WYŁĄCZNIK

DETAILED CARD



## TECHNICAL PARAMETERS

|   |         |
|---|---------|
| <b>Index:</b>                             | 247057  |
| <b>Ingress protection:</b>                | IP54    |
| <b>Impact resistance:</b>                 | IK10    |
| <b>Rated power of the luminaire [W]*:</b> | 32      |
| <b>Supply voltage [V]:</b>                | 220-240 |
| <b>Luminous flux [lm]*:</b>               | 4300    |
| <b>Energy efficiency class:</b>           | D       |
| <b>Electrical protection class:</b>       | I       |
| <b>Colour temperature [K]:</b>            | 4000    |

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm<sup>2</sup> (3 m) comes as standard.

## APPLICATION

The luminaire will provide precise illumination of the workplace.

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI SCHUKO WYŁĄCZNIK

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|  |            |                                   |                              |
|--|------------|-----------------------------------|------------------------------|
| <b>Index:</b>                            | 247057     | <b>Dimensions (H/W/T/S) [mm]:</b> | 300/400/100                  |
| <b>Light source:</b>                     | LED module | <b>Impact resistance:</b>         | IK10                         |
| <b>Nominal power [W]:</b>                | 32         | <b>Ingress protection:</b>        | IP54                         |
| <b>Rated power of the luminaire [W]:</b> | 32         | <b>Plug type:</b>                 | UNI-SCHUKO                   |
| <b>Supply voltage [V]:</b>               | 220-240    | <b>Socket type:</b>               | SCHUKO                       |
| <b>Luminous flux [lm]:</b>               | 4300       | <b>Sockets:</b>                   | 2                            |
| <b>Energy efficiency class:</b>          | D          | <b>Cable length [m]:</b>          | 5                            |
| <b>Electrical protection class:</b>      | I          | <b>Switch:</b>                    | yes                          |
| <b>Colour temperature [K]:</b>           | 4000       | <b>Net weight [kg]:</b>           | 2.900                        |
| <b>Beam angle [°]:</b>                   | 120        | <b>Category type:</b>             | workplace floodlights        |
| <b>Diffuser material:</b>                | PC         | <b>ETIM class:</b>                | EC000346                     |
| <b>Diffuser type:</b>                    | frozen     | <b>Technical Warranty:</b>        | 5                            |
| <b>Material of the body:</b>             | PP         | <b>CE certificate:</b>            | <a href="#">175/2023</a>     |
| <b>Colour of the body:</b>               | grey       | <b>Manual:</b>                    | <a href="#">Download PDF</a> |

# MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI SCHUKO WYŁĄCZNIK

DETAILED CARD

## ACCESSORIES AVAILABLE

| index  | Name                                       |
|--------|--|
| 000737 | FUTURE STAND Tripod with Click Head System |
| 000720 | Standard tripod                            |



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 18 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 175/2023