MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI SCHUKO WYŁĄCZNIK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	247057
Ingress protection:	IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Supply voltage [V]:	220-240
Luminous flux [lm]*:	4300
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.
A rubber cable H07RN-F 3x1.5 mm2 (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI SCHUKO WYŁĄCZNIK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	247057	**Dimensions (H/W/T/S) [mm]:**	300/400/100
Light source:	LED module	**Impact resistance:**	IK10
Nominal power [W]:	32	**Ingress protection:**	IP54
Rated power of the luminaire [W]:	32	**Plug type:**	UNI-SCHUKO
Supply voltage [V]:	220-240	**Socket type:**	SCHUKO
Luminous flux [lm]:	4300	**Sockets:**	2
Energy efficiency class:	D	**Cable length [m]:**	5
Electrical protection class:	I	**Switch:**	yes
Colour temperature [K]:	4000	**Net weight [kg]:**	2.900
Beam angle [°]:	120	**Category type:**	workplace floodlights
Diffuser material:	PC	**ETIM class:**	EC000346
Diffuser type:	frozen	**Technical Warranty:**	5
Material of the body:	PP	**CE certificate:**	175/2023
Colour of the body:	grey	**Manual:**	Download PDF

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI SCHUKO WYŁĄCZNIK


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 175/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl