MAGNUM FUTURE 32W II KLASA SZARY CH

DETAILED CARD



TECHNICAL PARAMETERS

Index:	247217
Ingress protection:	IP44
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Supply voltage [V]:	220-240
Luminous flux [lm]*:	4300
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	4000

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.
A rubber cable H07RN-F 3x1.5 mm2 (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W II KLASA SZARY CH

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	247217
Light source:	LED module
Nominal power [W]:	32
Rated power of the luminaire [W]:	32
Supply voltage [V]:	220-240
Luminous flux [lm]:	4300
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	4000
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	frozen
Material of the body:	PP

Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	300/400/100
Impact resistance:	IK10
Ingress protection:	IP44
Plug type:	CH
Cable length [m]:	5
Net weight [kg]:	2.600
Category type:	workplace floodlights
ETIM class:	EC000347
Technical Warranty:	5
CE certificate:	175/2023
Manual:	Download PDF

MAGNUM FUTURE 32W II KLASA SZARY CH


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 175/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl