MAGNUM FUTURE 32W III KL. OCHR. SZARY 24V CEE

DETAILED CARD



TECHNICAL PARAMETERS

Index:	247262
Ingress protection:	IP44
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Supply voltage [V]:	24
Luminous flux [lm]*:	4300
Energy efficiency class:	D
Electrical protection class:	III
Colour temperature [K]:	4000

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.
A rubber cable H07RN-F 3x1.5 mm2 (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W III KL. OCHR. SZARY 24V CEE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	32
Supply voltage [V]:	24
Luminous flux [lm]:	4300
Energy efficiency class:	D
Electrical protection class:	III
Colour temperature [K]:	4000
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	frozen
Material of the body:	PP

Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	300/400/100
Impact resistance:	IK10
Ingress protection:	IP44
Plug type:	CEE
Cable length [m]:	5
Net weight [kg]:	2.600
Index:	247262
Category type:	workplace floodlights
ETIM class:	EC000347
Manual:	Download PDF

MAGNUM FUTURE 32W III KL. OCHR. SZARY 24V CEE


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 177/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl