

MAGNUM FUTURE 32W III KL. OCHR. SZARY 42V CEE

DETAILED CARD



TECHNICAL PARAMETERS

Index:	247248
Ingress protection:	IP44
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Supply voltage [V]:	42-48
Luminous flux [lm]*:	4300
Energy efficiency class:	D
Electrical protection class:	III
Colour temperature [K]:	4000

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm² (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W III KL. OCHR. SZARY 42V CEE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	247248	Electrical protection class:	III
Nominal power [W]:	32	Ingress protection:	IP44
Colour temperature [K]:	4000	Beam angle [°]:	120
Light source:	LED module	Diffuser material:	PC
Luminous flux [lm]:	4300	Diffuser type:	frozen
Rated power of the luminaire [W]:	32	Material of the body:	PP
Plug type:	CEE	Colour of the body:	grey
Supply voltage [V]:	42-48	Dimensions (H/W/T/S) [mm]:	300/400/100
Cable length [m]:	5	Impact resistance:	IK10
Energy efficiency class:	D	Net weight [kg]:	2.800
		Category type:	workplace floodlights
		ETIM class:	EC000347
		Technical Warranty:	5
		CE certificate:	178/2023
		Manual:	Download PDF

MAGNUM FUTURE 32W III KL. OCHR. SZARY 42V CEE

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 18 July 2024
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 178/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl