

MAGNUM FUTURE 32W III KL. OCHR. SZARY 42V Z GNIAZDAMI CEE (2-PIN)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	247255
Ingress protection:	IP44
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Supply voltage [V]:	42-48
Luminous flux [lm]*:	4300
Energy efficiency class:	D
Electrical protection class:	III
Colour temperature [K]:	4000

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm² (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W III KL. OCHR. SZARY 42V Z GNIAZDAMI CEE (2-PIN)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	247255	Electrical protection class:	III
Nominal power [W]:	32	Ingress protection:	IP44
Colour temperature [K]:	4000	Beam angle [°]:	120
Light source:	LED module	Diffuser material:	PC
Luminous flux [lm]:	4300	Diffuser type:	frozen
Rated power of the luminaire [W]:	32	Material of the body:	PP
Plug type:	CEE	Colour of the body:	grey
Supply voltage [V]:	42-48	Dimensions (H/W/T/S) [mm]:	300/400/100
Socket type:	CEE (2-PIN)	Impact resistance:	IK10
Sockets:	2	Net weight [kg]:	2.800
Cable length [m]:	5	Category type:	workplace floodlights
Energy efficiency class:	D	ETIM class:	EC000347
		Technical Warranty:	5
		CE certificate:	178/2023
		Manual:	Download PDF

MAGNUM FUTURE 32W III KL. OCHR. SZARY 42V Z GNIAZDAMI CEE (2-PIN)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)