MAGNUM FUTURE 32W SZARY 110V CEE

DETAILED CARD



TECHNICAL PARAMETERS

Index:	247231
Ingress protection:	IP44
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Supply voltage [V]:	110
Luminous flux [lm]*:	4300
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.
A rubber cable H07RN-F 3x1.5 mm2 (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W SZARY 110V CEE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	247231	**Dimensions (H/W/T/S) [mm]:**	300/400/100
Light source:	LED module	**Impact resistance:**	IK10
Nominal power [W]:	32	**Ingress protection:**	IP44
Rated power of the luminaire [W]:	32	**Plug type:**	CEE
Supply voltage [V]:	110	**Socket type:**	CEE
Luminous flux [lm]:	4300	**Sockets:**	2
Energy efficiency class:	D	**Cable length [m]:**	5
Electrical protection class:	I	**Net weight [kg]:**	2.600
Colour temperature [K]:	4000	**Category type:**	workplace floodlights
Beam angle [°]:	120	**ETIM class:**	EC000346
Diffuser material:	PC	**Technical Warranty:**	5
Diffuser type:	frozen	**CE certificate:**	176/2023
Material of the body:	PP	**Manual:**	Download PDF
Colour of the body:	grey		

MAGNUM FUTURE 32W SZARY 110V CEE


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 176/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl