

MAGNUM FUTURE 32W SZARY 110V CEE

DETAILED CARD



TECHNICAL PARAMETERS

Index:	247231
Ingress protection:	IP44
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Supply voltage [V]:	110
Luminous flux [lm]*:	4300
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm² (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W SZARY 110V CEE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	247231	Electrical protection class:	I
Nominal power [W]:	32	Ingress protection:	IP44
Colour temperature [K]:	4000	Beam angle [°]:	120
Light source:	LED module	Diffuser material:	PC
Luminous flux [lm]:	4300	Diffuser type:	frozen
Rated power of the luminaire [W]:	32	Material of the body:	PP
Plug type:	CEE	Colour of the body:	grey
Supply voltage [V]:	110	Dimensions (H/W/T/S) [mm]:	300/400/100
Socket type:	CEE	Impact resistance:	IK10
Sockets:	2	Net weight [kg]:	2.600
Cable length [m]:	5	Category type:	workplace floodlights
Energy efficiency class:	D	ETIM class:	EC000346
		Technical Warranty:	5
		CE certificate:	176/2023
		Manual:	Download PDF

MAGNUM FUTURE 32W SZARY 110V CEE

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)