

MAGNUM FUTURE ACCU 32W UNI-SCHUKO

DETAILED CARD



TECHNICAL PARAMETERS

Index:	247125
Ingress protection:	IP54/20
Impact resistance:	IK10
Nominal power [W]:	32
Colour temperature [K]:	4000
Luminous flux [lm]*:	3300
Supply voltage [V]:	220-240
Energy efficiency class:	E
Electrical protection class:	II
Material of the body:	PP

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE ACCU 32W UNI-SCHUKO

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Diffuser colour:	white
Nominal power [W]:	32	Material of the body:	PP
Supply voltage [V]:	220-240	Colour of the body:	grey
Frequency [Hz]:	50 - 60	Dimensions (H/W/T/S) [mm]:	300/400/100
Luminous flux [lm]:	3300	Impact resistance:	IK10
Energy efficiency class:	E	Ingress protection:	IP54/20
Electrical protection class:	II	Working temperature [°C]:	from 0 to +25
Colour temperature [K]:	4000	Cable length [m]:	5
Colour rendering index:	>80	Net weight [kg]:	2.450
SDCM:	≤ 3	Warranty [years]:	2
Charging time [h:min]:	4.00	Index:	247125
Battery life [h:min]:	6.00	EAN:	5905963247125
Beam angle [°]:	120	Category type:	workplace floodlights
Battery:	Li-Ion 18,5V	LED lifespan L70B50 [h]:	50000
Battery capacity [mAh]:	2000	ETIM class:	EC000347
Diffuser material:	PC	Manual:	Download PDF
Diffuser type:	MAT		

MAGNUM FUTURE ACCU 32W UNI-SCHUKO

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 182/2023