

# MAGNUM FUTURE 50W II KL. SZARY UNI-SCHUKO II KLASA

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP54
<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]*:</b>	50
<b>Colour temperature [K]:</b>	4000
<b>Luminous flux [lm]*:</b>	6500
<b>Supply voltage [V]:</b>	220-240
<b>Energy efficiency class:</b>	D
<b>Electrical protection class:</b>	II
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

A rubber cable H07RN-F 3x1,5 mm<sup>2</sup> (5 m) comes as standard.

## APPLICATION

With a variety of functions, the lamp is ideal for illuminating any workplace. The high luminous flux and maximum degree of impact resistance are especially important for lighting construction sites or for the work of services intervening in various emergencies. A high degree of waterproofness allows its use in the harshest weather conditions. The multi-position arm and numerous accessories provide a wide range of mounting options so as to precisely direct the light beam, leaving the worker's hands free. Its small size and light weight make it easy to use in workshops, car showrooms, to illuminate the workplace in industrial halls or finishing work.

# MAGNUM FUTURE 50W II KL. SZARY UNI-SCHUKO II KLASA

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	247408	<b>Colour of the body:</b>	grey
<b>Rated power of the luminaire [W]:</b>	50	<b>Dimensions (H/W/T/S) [mm]:</b>	300/480/75
<b>Colour temperature [K]:</b>	4000	<b>Impact resistance:</b>	IK10
<b>Light source:</b>	LED module	<b>Ingress protection:</b>	IP54
<b>Luminous flux [lm]:</b>	6500	<b>Cable length [m]:</b>	5
<b>Diffuser type:</b>	frozen	<b>Net weight [kg]:</b>	3.300
<b>Plug type:</b>	UNI-SCHUKO	<b>Category type:</b>	workplace floodlights
<b>Supply voltage [V]:</b>	220-240	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Luminous efficacy [lm/W]:</b>	153	<b>CE certificate:</b>	<a href="#">120/2023</a>
<b>Energy efficiency class:</b>	D	<b>Beam angle [°]:</b>	120
<b>Electrical protection class:</b>	II	<b>Material of the body:</b>	PP
<b>Diffuser material:</b>	PC	<b>ETIM class:</b>	EC000347

Card creation date: 13 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 120/2023