

MAGNUM FUTURE LITE 32W I KL. OCHR. DK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	406232
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	32
Colour temperature [K]:	4000
Luminous flux [lm]*:	3600
Supply voltage [V]:	220-240
Electrical protection class:	I
Material of the body:	PP
Colour of the body:	green

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE LITE 32W I KL. OCHR. DK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	32	Material of the body:	PP
Light source:	LED module	Colour of the body:	green
Colour temperature [K]:	4000	Dimensions (H/W/T/S) [mm]:	300/400/100
Luminous flux [lm]:	3600	Ingress protection:	IP44
Plug type:	DK	Impact resistance:	IK10
Supply voltage [V]:	220-240	Wire type:	H07RN-F 2×1,0mm
Electrical protection class:	I	Net weight [kg]:	2.600
Beam angle [°]:	120	Index:	406232
Diffuser material:	PC	Category type:	workplace floodlights
Cable length [m]:	3	Warranty [years]:	2
Diffuser type:	frozen	Manual:	Download PDF
		Energy efficiency class:	E
		ETIM class:	EC000346

MAGNUM FUTURE LITE 32W I KL. OCHR. DK

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 139/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl