MAGNUM FUTURE LITE 50W I KL. OCHR. DK

DETAILED CARD





TECHNICAL PARAMETERS

Index:	406256
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	50
Colour temperature [K]:	4000
Luminous flux [lm]*:	5500
Supply voltage [V]:	220-240
Electrical protection class:	1
Material of the body:	PP
Colour of the body:	green

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The family of durable and handy MAGNUM FUTURE LED XL luminaires has been designed to illuminate larger areas.



MAGNUM FUTURE LITE 50W I KL. OCHR. DK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	50
Colour temperature [K]:	4000
Luminous flux [Im]:	5500
Supply voltage [V]:	220-240
Electrical protection class:	1
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	frozen
Material of the body:	PP
Colour of the body:	green
Dimensions (H/W/T/S) [mm]:	300/480/75

Impact resistance:	IK10
Ingress protection:	IP44
Plug type:	DK
Cable length [m]:	3
Net weight [kg]:	3.300
Index:	406256
Category type:	workplace floodlights
Warranty [years]:	2
Manual:	Download PDF
Energy efficiency class:	E
ETIM class:	EC000346




MAGNUM FUTURE LITE 50W I KL. OCHR. DK

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod





FUTURE STAND Tripod with Click Head System (000737)

Standard tripod (000720)

Card creation date: 08 November 2023



