# MAGNUM FUTURE LITE 50W I KL. OCHR. DK

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Index:** | 406256 |
| **Ingress protection:** | IP44 |
| **Impact resistance:** | IK10 |
| **Nominal power [W]:** | 50 |
| **Colour temperature [K]:** | 4000 |
| **Luminous flux [lm]*:** | 5500 |
| **Supply voltage [V]:** | 220-240 |
| **Electrical protection class:** | I |
| **Material of the body:** | PP |
| **Colour of the body:** | green |

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

## APPLICATION

The family of durable and handy MAGNUM FUTURE LED XL luminaires has been designed to illuminate larger areas.

# MAGNUM FUTURE LITE 50W I KL. OCHR. DK

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | | | |
|---|---|---|---|
| **Light source:** | LED module | **Impact resistance:** | IK10 |
| **Nominal power [W]:** | 50 | **Ingress protection:** | IP44 |
| **Colour temperature [K]:** | 4000 | **Plug type:** | DK |
| **Luminous flux [lm]:** | 5500 | **Cable length [m]:** | 3 |
| **Supply voltage [V]:** | 220-240 | **Net weight [kg]:** | 3.300 |
| **Electrical protection class:** | I | **Index:** | 406256 |
| **Beam angle [°]:** | 120 | **Category type:** | workplace floodlights |
| **Diffuser material:** | PC | **Warranty [years]:** | 2 |
| **Diffuser type:** | frozen | **Manual:** | Download PDF |
| **Material of the body:** | PP | **Energy efficiency class:** | E |
| **Colour of the body:** | green | **ETIM class:** | EC000346 |
| **Dimensions (H/W/T/S) [mm]:** | 300/480/75 | | |

# MAGNUM FUTURE LITE 50W I KL. OCHR. DK


DETAILED CARD

## ACCESSORIES AVAILABLE

| index | Name |
|---|---|
| 000737 | FUTURE STAND Tripod with Click Head System |
| 000720 | Standard tripod |



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)



The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 139/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl