

# MAGNUM FUTURE LITE 50W II KL. OCHR. UNI-SCHUKO

DETAILED CARD



## TECHNICAL PARAMETERS

|                                     |         |
|-------------------------------------|---------|
| <b>Index:</b>                       | 406294  |
| <b>Ingress protection:</b>          | IP54    |
| <b>Impact resistance:</b>           | IK10    |
| <b>Nominal power [W]:</b>           | 50      |
| <b>Colour temperature [K]:</b>      | 4000    |
| <b>Luminous flux [lm]*:</b>         | 5500    |
| <b>Supply voltage [V]:</b>          | 220-240 |
| <b>Electrical protection class:</b> | II      |
| <b>Material of the body:</b>        | PP      |
| <b>Colour of the body:</b>          | green   |

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

## APPLICATION

The family of durable and handy MAGNUM FUTURE LED XL luminaires has been designed to illuminate larger areas.

# MAGNUM FUTURE LITE 50W II KL. OCHR. UNI-SCHUKO

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                              |            |                          |                              |
|------------------------------|------------|--------------------------|------------------------------|
| Light source:                | LED module | Impact resistance:       | IK10                         |
| Nominal power [W]:           | 50         | Ingress protection:      | IP54                         |
| Colour temperature [K]:      | 4000       | Plug type:               | UNI-SCHUKO                   |
| Luminous flux [lm]:          | 5500       | Cable length [m]:        | 3                            |
| Supply voltage [V]:          | 220-240    | Net weight [kg]:         | 3.300                        |
| Electrical protection class: | II         | Index:                   | 406294                       |
| Beam angle [°]:              | 120        | Category type:           | workplace floodlights        |
| Diffuser material:           | PC         | Warranty [years]:        | 2                            |
| Diffuser type:               | frozen     | Manual:                  | <a href="#">Download PDF</a> |
| Material of the body:        | PP         | Energy efficiency class: | E                            |
| Colour of the body:          | green      | ETIM class:              | EC000346                     |
| Dimensions (H/W/T/S) [mm]:   | 300/480/75 |                          |                              |

# MAGNUM FUTURE LITE 50W II KL. OCHR. UNI-SCHUKO

DETAILED CARD

## ACCESSORIES AVAILABLE

| index  | Name                                       |
|--------|--|
| 000737 | FUTURE STAND Tripod with Click Head System |
| 000720 | Standard tripod                            |



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 139/2023