# MAGNUM FUTURE LITE 50W II KL. OCHR. UNI-SCHUKO

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

Index:	406294
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	50
Colour temperature [K]:	4000
Luminous flux [lm]*:	5500
Supply voltage [V]:	220-240
Electrical protection class:	II
Material of the body:	PP
Colour of the body:	green

#### **CHARACTERISTICS**

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

## **APPLICATION**

The family of durable and handy MAGNUM FUTURE LED XL luminaires has been designed to illuminate larger areas.



# MAGNUM FUTURE LITE 50W II KL. OCHR. UNI-SCHUKO

**DETAILED CARD** 

### **TECHNICAL PARAMETERS TABLE**

Nominal power [W]:	50
Light source:	LED module
Colour temperature [K]:	4000
Luminous flux [Im]:	5500
Plug type:	UNI-SCHUKO
Supply voltage [V]:	220-240
Electrical protection class:	II
Beam angle [°]:	120
Cable length [m]:	3
Diffuser material:	PC
Diffuser type:	frozen

Material of the body:	PP
Colour of the body:	green
Ingress protection:	IP54
Dimensions (H/W/T/S) [mm]:	300/480/75
Impact resistance:	IK10
Net weight [kg]:	3.300
Index:	406294
Category type:	workplace floodlights
Warranty [years]:	2
Manual:	Download PDF
Energy efficiency class:	E
ETIM class:	EC000346



# MAGNUM FUTURE LITE 50W II KL. OCHR. UNI-SCHUKO

**DETAILED CARD** 

#### **ACCESSORIES AVAILABLE**

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod





FUTURE STAND Tripod with Click Head System (000737)

Standard tripod (000720)

Card creation date: 08 November 2023



