

# MAGNUM FUTURE LITE 78W I KL. OCHR. DK

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP44
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	78
<b>Colour temperature [K]:</b>	4000
<b>Luminous flux [lm]*:</b>	9500
<b>Supply voltage [V]:</b>	220-240
<b>Electrical protection class:</b>	I
<b>Material of the body:</b>	PP
<b>Colour of the body:</b>	green
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

## APPLICATION

The family of durable and handy MAGNUM FUTURE LED XL luminaires has been designed to illuminate larger areas.

# MAGNUM FUTURE LITE 78W I KL. OCHR. DK

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Material of the body:	PP
Nominal power [W]:	78	Colour of the body:	green
Colour temperature [K]:	4000	Ingress protection:	IP44
Luminous flux [lm]:	9500	Dimensions (H/W/T/S) [mm]:	300/480/75
Plug type:	DK	Impact resistance:	IK10
Supply voltage [V]:	220-240	Net weight [kg]:	3.300
Electrical protection class:	I	Index:	406300
Beam angle [°]:	120	Category type:	workplace floodlights
Cable length [m]:	3	Warranty [years]:	2
Diffuser material:	PC	Manual:	<a href="#">Download PDF</a>
Diffuser type:	frozen	Energy efficiency class:	D
		ETIM class:	EC000346

# MAGNUM FUTURE LITE 78W I KL. OCHR. DK

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 139/2023