

MAGNUM FUTURE LITE 78W I KL. OCHR. Z GNIAZDEM SCHUKO

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	78
Colour temperature [K]:	4000
Luminous flux [lm]*:	9500
Supply voltage [V]:	220-240
Electrical protection class:	I
Material of the body:	PP
Colour of the body:	green
Diffuser material:	PC

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The family of durable and handy MAGNUM FUTURE LED XL luminaires has been designed to illuminate larger areas.

MAGNUM FUTURE LITE 78W I KL. OCHR. Z GNIAZDEM SCHUKO

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Material of the body:	PP
Nominal power [W]:	78	Colour of the body:	green
Colour temperature [K]:	4000	Ingress protection:	IP54
Luminous flux [lm]:	9500	Dimensions (H/W/T/S) [mm]:	300/480/75
Plug type:	UNI-SCHUKO	Impact resistance:	IK10
Supply voltage [V]:	220-240	Net weight [kg]:	3.400
Socket type:	SCHUKO	Index:	406324
Electrical protection class:	I	Category type:	workplace floodlights
Sockets:	1	Warranty [years]:	2
Beam angle [°]:	120	Manual:	Download PDF
Cable length [m]:	3	Energy efficiency class:	D
Diffuser material:	PC	ETIM class:	EC000346
Diffuser type:	frozen		

MAGNUM FUTURE LITE 78W I KL. OCHR. Z GNIAZDEM SCHUKO


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)




Standard tripod (000720)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 139/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl