

# MAGNUM FUTURE 20W 120ST UNI-SCHUKO

DETAILED CARD



## TECHNICAL PARAMETERS

|                                     |         |
|-------------------------------------|---------|
| <b>Index:</b>                       | 248351  |
| <b>Ingress protection:</b>          | IP54    |
| <b>Impact resistance:</b>           | IK10    |
| <b>Nominal power [W]:</b>           | 20      |
| <b>Colour temperature [K]:</b>      | 4000    |
| <b>Luminous flux [lm]*:</b>         | 2300    |
| <b>Supply voltage [V]:</b>          | 220-240 |
| <b>Electrical protection class:</b> | II      |
| <b>Material of the body:</b>        | PP      |
| <b>Colour of the body:</b>          | grey    |

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Made of impact-resistant polipropylene (PP). Anti-glare diffuser which transmits up to 80% of the light emitted by the diodes. The smaller size and compact design make it convenient to transport. It is equipped with a movable, multi-position arm also acting as a hook. Multi-purpose mounting bracket included.

It can be mounted on a Future Stand, significantly increasing the range and comfort of use.

## APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.

# MAGNUM FUTURE 20W 120ST UNI-SCHUKO

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                              |            |                            |                              |
|------------------------------|------------|----------------------------|------------------------------|
| Nominal power [W]:           | 20         | Material of the body:      | PP                           |
| Light source:                | LED module | Ingress protection:        | IP54                         |
| Colour temperature [K]:      | 4000       | Colour of the body:        | grey                         |
| Luminous flux [lm]:          | 2300       | Impact resistance:         | IK10                         |
| Plug type:                   | UNI-SCHUKO | Net weight [kg]:           | 0.900                        |
| Supply voltage [V]:          | 220-240    | Index:                     | 248351                       |
| Electrical protection class: | II         | Category type:             | workplace floodlights        |
| Beam angle [°]:              | 120        | Dimensions (H/W/T/S) [mm]: | 192/193/123                  |
| Cable length [m]:            | 3          | Energy efficiency class:   | D                            |
| Diffuser material:           | PC         | ETIM class:                | EC000347                     |
| Diffuser type:               | frozen     | CE certificate:            | <a href="#">173/2023</a>     |
|                              |            | Manual:                    | <a href="#">Download PDF</a> |

# MAGNUM FUTURE 20W 120ST UNI-SCHUKO

DETAILED CARD

## ACCESSORIES AVAILABLE

| index  | Name                                       |
|--------|--------------------------------------------|
| 000737 | FUTURE STAND Tripod with Click Head System |
| 000720 | Standard tripod                            |



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 08 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 173/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl