

MAGNUM FUTURE 20W 45 ST 42-48V CEE

DETAILED CARD



TECHNICAL PARAMETERS

Index:	248726
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	20
Colour temperature [K]:	4000
Luminous flux [lm]*:	2300
Supply voltage [V]:	42-48
Electrical protection class:	III
Material of the body:	PP
Colour of the body:	grey

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Made of impact-resistant polipropylene (PP). Anti-glare diffuser which transmits up to 80% of the light emitted by the diodes. The smaller size and compact design make it convenient to transport. It is equipped with a movable, multi-position arm also acting as a hook. Multi-purpose mounting bracket included.

It can be mounted on a Future Stand, significantly increasing the range and comfort of use.

APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.

MAGNUM FUTURE 20W 45 ST 42-48V CEE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ingress protection:	IP44
Nominal power [W]:	20	Plug type:	CEE
Colour temperature [K]:	4000	Cable length [m]:	3
Luminous flux [lm]:	2300	Net weight [kg]:	1
Supply voltage [V]:	42-48	Index:	248726
Electrical protection class:	III	Category type:	workplace floodlights
Beam angle [°]:	45	Dimensions (H/W/T/S) [mm]:	192/193/123
Diffuser material:	PC	Energy efficiency class:	D
Diffuser type:	frozen	ETIM class:	EC000347
Material of the body:	PP	CE certificate:	173/2023
Colour of the body:	grey	Manual:	Download PDF
Impact resistance:	IK10		

MAGNUM FUTURE 20W 45 ST 42-48V CEE

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)