MAGNUM FUTURE 20W 45ST 24V CEE

DETAILED CARD





TECHNICAL PARAMETERS

Index:	248733
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	20
Colour temperature [K]:	4000
Luminous flux [lm]*:	2300
Supply voltage [V]:	24
Electrical protection class:	III
Material of the body:	PP
Colour of the body:	grey

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Made of impact-resistant polipropylene (PP). Anti-glare diffuser which transmits up to 80% of the light emitted by the diodes. The smaller size and compact design make it convenient to transport. It is equipped with a movable, multi-position arm also acting as a hook. Multi-purpose mounting bracket included.

It can be mounted on a Future Stand, significantly increasing the range and comfort of use.

APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.



MAGNUM FUTURE 20W 45ST 24V CEE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	20
Colour temperature [K]:	4000
Luminous flux [lm]:	2300
Supply voltage [V]:	24
Electrical protection class:	III
Beam angle [°]:	45
Diffuser material:	PC
Diffuser type:	frozen
Material of the body:	PP
Colour of the body:	grey
Impact resistance:	IK10

Ingress protection:	IP44
Plug type:	CEE
Cable length [m]:	3
Net weight [kg]:	1
Index:	248733
Category type:	workplace floodlights
Dimensions (H/W/T/S) [mm]:	192/193/123
Energy efficiency class:	D
ETIM class:	EC000347
CE certificate:	<u>173/2023</u>
Manual:	Download PDF




MAGNUM FUTURE 20W 45ST 24V CEE

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
000720	Standard tripod





FUTURE STAND Tripod with Click Head System (000737)

Standard tripod (000720)

Card creation date: 08 November 2023



