

MAGNUM FUTURE ACCU 20W 45 ST

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|-------------------------------------|---------|
| Index: | 248818 |
| Ingress protection: | IP54/20 |
| Impact resistance: | IK10 |
| Nominal power [W]: | 20 |
| Colour temperature [K]: | 4000 |
| Luminous flux [lm]*: | 2000 |
| Supply voltage [V]: | 220-240 |
| Energy efficiency class: | E |
| Electrical protection class: | II |
| Material of the body: | PP |

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

It can be mounted on a Future Stand, significantly increasing the range and comfort of use.

APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.

MAGNUM FUTURE ACCU 20W 45 ST

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|--------------|----------------------------|------------------------------|
| Nominal power [W]: | 20 | Diffuser type: | frozen |
| Light source: | LED module | Diffuser colour: | white |
| Colour temperature [K]: | 4000 | Material of the body: | PP |
| Rated power of the luminaire [W]: | 21 | Colour of the body: | grey |
| Luminous flux [lm]: | 2000 | Dimensions (H/W/T/S) [mm]: | 192/193/123 |
| Beam angle [°]: | 45 | Impact resistance: | IK10 |
| Supply voltage [V]: | 220-240 | Ingress protection: | IP54/20 |
| Frequency [Hz]: | 50 - 60 | Working temperature [°C]: | from 0 to +25 |
| Cable length [m]: | 2 | Wire type: | PCV |
| Switch: | yes | Net weight [kg]: | 1.100 |
| Energy efficiency class: | E | Warranty [years]: | 2 |
| Electrical protection class: | II | Index: | 248818 |
| Colour rendering index: | >80 | EAN: | 5905963248818 |
| SDCM: | ≤ 3 | Category type: | workplace floodlights |
| Battery: | Li-Ion 18,5V | LED lifespan L70B50 [h]: | 50000 |
| Battery capacity [mAh]: | 2000 | ETIM class: | EC000347 |
| Diffuser material: | PC | Manual: | Download PDF |

MAGNUM FUTURE ACCU 20W 45 ST

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|--|
| 000737 | FUTURE STAND Tripod with Click Head System |
| 000720 | Standard tripod |
| 315039 | Set of magnets for Magnum XS (2 pcs.) |



FUTURE STAND Tripod with Click Head System (000737)



Standard tripod (000720)

Card creation date: 04 August 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 174/2023