

DIONE LED PLUS ASYMMETRIC 2300LM 840 IP65 I KL. OPAL WHITE VANDALPROOF 21W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	940644
Nominal power [W]:	21
Luminous flux [lm]*:	2300
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	Biały
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel and asymmetrical light distribution. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS ASYMMETRIC 2300LM 840 IP65 I KL. OPAL WHITE VANDALPROOF 21W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	21	Ingress protection:	IP65
Index:	940644	Working temperature [°C]:	from -20 to +35
Colour temperature [K]:	4000	Emergency lighting [h]:	0
Luminous flux [lm]:	2300	Vandalproof:	yes
Light source:	LED module	Dimensions of single box [mm]:	340/340/115
Diffuser type:	OPAL	Net weight [kg]:	43831
Rated power of the luminaire [W]:	22	Warranty [years]:	5
Supply voltage [V]:	220-240	Permeability factor of the diffuser:	0.73
Frequency [Hz]:	50 - 60	Category type:	bulkheads
Luminous efficacy [lm/W]:	105	Category of application:	commercial facilities, educational institutions
Energy efficiency class:	E	AC voltage range [V]:	198-264
Electrical protection class:	I	DC voltage range [V]:	176-280
Colour rendering index:	>80	LED lifespan L70B50 [h]:	115000
SDCM:	≤ 3	LED lifespan L80B20 [h]:	75000
Power factor:	0.94	LED lifespan L90B10 [h]:	33000
Beam angle [°]:	120	Light distribution type:	asymmetric
Surge protection [kV]:	1	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PC	CE certificate:	380/2023
Diffuser colour:	white	Warranty [years]:	5
Optics material:	ABS	Manual:	Download PDF
Material of the body:	ABS	PZH certificate:	B-BK-60212-0619/20
Colour of the body:	white	ENEC Certificate:	PL BBJ/011/2021/M1/A1
Ring material:	Biały	Plik LDT:	
Ring colour:	340/115		
Dimensions (H/W/T/S) [mm]:	340/115		
Impact resistance:	IK10		

DIONE LED PLUS ASYMMETRIC 2300LM 840 IP65 I KL. OPAL WHITE VANDALPROOF 21W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white
matt RAL 9003 painted vandal
resistant (120DL118)

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 380/2023