

DIONE LED 2300LM 840 IP65 I KL. OPAL WHITE

VANDALPROOF 24W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	940521
Ingress protection:	IP65
Impact resistance:	IK10
Rated power of the luminaire [W]*:	27
Luminous flux [lm]*:	2300
Colour temperature [K]:	4000
SDCM:	≤ 5
Energy efficiency class:	F
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy-saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Its base and ring are made of UV-resistant material. Specially profiled diffuser made of vandal-resistant PC allows keeping the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. The fitting is offered in RCR version:
- sensor is used to detect motion; for detection uses microwaves (active sensor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED 2300LM 840 IP65 I KL. OPAL WHITE

VANDALPROOF 24W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	940521	Ring colour:	white
EAN:	952678	Dimensions (H/W/T/S) [mm]:	ø340/115
Light source:	LED module	Impact resistance:	IK10
Nominal power [W]:	24	Ingress protection:	IP65
Rated power of the luminaire [W]:	27	Working temperature [°C]:	from -20 to +25
Frequency [Hz]:	50 - 60	Dimensions of single box [mm]:	340/340/115
Luminous flux [lm]:	2300	Number on the palette [pcs]:	80
Luminous efficacy [lm/W]:	81	Net weight [kg]:	42005
Energy efficiency class:	F	Permeability factor of the diffuser:	0.73
Electrical protection class:	I	Category type:	bulkheads
Colour temperature [K]:	4000	Light distribution type:	open space
Colour rendering index:	>80	LED lifespan L70B50 [h]:	110000
SDCM:	≤ 5	LED lifespan L80B20 [h]:	80000
Power factor:	0.90	LED lifespan L90B10 [h]:	40000
Beam angle [°]:	120	Optics material:	ABS
Diffuser material:	PC	Vandalproof:	yes
Diffuser type:	OPAL	Warranty [years]:	2
Diffuser colour:	white	CE certificate:	20/2022
Material of the body:	ABS	PZH certificate:	B-BK-60212-0619/20
Colour of the body:	white	Manual:	Download PDF
Ring material:	ABS		

DIONE LED 2300LM 840 IP65 I KL. OPAL WHITE VANDALPROOF 24W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white
matt RAL 9003 painted vandal
resistant (120DL118)

Card creation date: 26 July 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 20/2022



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl