

# TYTAN 2 LED 24-48V 1150MM 2750LM 840 IP66 19W

## DETAILED CARD



### TECHNICAL PARAMETERS

<b>Index:</b>	355165
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK09
<b>Nominal power [W]:</b>	19
<b>Luminous flux [lm]*:</b>	2750
<b>Colour temperature [K]:</b>	4000
<b>Material of the body:</b>	PC
<b>Colour of the body:</b>	grey
<b>Diffuser type:</b>	MAT
<b>Mounting version:</b>	surface, suspended

### CHARACTERISTICS

TYTAN 2 LED is a fitting from NEXT GEN line, which is a new generation of fittings in LED technology. The fitting, designed from scratch, allows new solutions improving the light distribution and temperature balance. Branded LED diodes and new LED modules have influence on a very high luminous efficacy: 123 lm/W. It guarantees the best required lighting level and energy saving up to 68%. The solution based on integration of the diffuser and LED module is applied in the fitting. The fitting has a lot of facilities making the mounting easier and faster: the system of diffuser suspension, adjustable mounting brackets ensuring the mounting tolerance +/-50mm. Standard equipment of the fitting: clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation.

### APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.

# TYTAN 2 LED 24-48V 1150MM 2750LM 840 IP66 19W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	355165	Dimensions (H/W/T/S) [mm]:	1152/80/85
EAN:	5905963355165	Impact resistance:	IK09
Light source:	LED module	Ingress protection:	IP66
Nominal power [W]:	19	Mounting version:	surface, suspended
Rated power of the luminaire [W]:	22.30	Net weight [kg]:	1
Supply voltage [V]:	24 - 48	Warranty [years]:	2
Frequency [Hz]:	50 - 60	Category type:	battens
Luminous flux [lm]:	2750	Version:	INOX
Luminous efficacy [lm/W]:	123	AC voltage range [V]:	24 - 48
Energy efficiency class:	D	DC voltage range [V]:	24 - 48
Electrical protection class:	III	LED lifespan L70B50 [h]:	116000
Colour temperature [K]:	4000	LED lifespan L80B20 [h]:	72000
Colour rendering index:	>80	LED lifespan L90B10 [h]:	35000
SDCM:	≤ 3	Warranty [years]:	2
Power factor:	0.95	CE certificate:	135/2023
Diffuser type:	MAT	PZH certificate:	B-BK-60212-0152/20
Material of the body:	PC	HACCP:	852/2004
Colour of the body:	grey	Manual:	Download PDF

## LIGHT CURVES



# TYTAN 2 LED 24-48V 1150MM 2750LM 840 IP66 19W

DETAILED CARD

## TECHNICAL DETAILS



regulowane uchwyty / adjustable  
handles / einstellbare Halterungen



system zwieszania klosza / suspension  
system of the diffuser / hängende  
Diffusor



wybór miejsca zasilania / choosing a  
place of power supply /  
Stromversorgungsanschluss von  
mehreren Seite möglich

# TYTAN 2 LED 24-48V 1150MM 2750LM 840 IP66 19W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
60000006	M16 stuffing box plug various PA black M-16 - BPM-21
908231	TYTAN LED - holder
80000279	Gland. beam, Codar, soft polyvinyl chloride (PVC-P), gray



M16 stuffing box plug various PA black  
M-16 - BPM-21 (60000006)

Card creation date:13 June 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 135/2023