

# MITRA LED BASIC 3850LM 4000K MAT IP66 I KL. (45W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	957116
Ingress protection:	IP66
Rated power of the luminaire [W]*:	45
Luminous flux [lm]*:	3850
Colour temperature [K]:	4000
SDCM:	≤ 5
Colour rendering index:	80
Electrical protection class:	I
Energy efficiency class:	F
Material of the body:	PP+FG

## CHARACTERISTICS

LED fitting with high luminous efficiency and an energy-saving, integrated LED panel. Body made of polypropylene (PP) with glass fiber (GF), aluminum handle and polycarbonate diffuser (PC).

The lamp is available with general G1 light distribution - with a frozen diffuser.

IP66 ingress protection class and IK07 impact-rating features make this fitting shock-resistant (vandal-resistant). The integrated handle allows for top mounting to the pole. Colour of the body: gray (RAL 7010).

Standard equipped with:

- surge protection (SP10kV),
- H07RN-F cable with a length of 0.6m.

## APPLICATION

Fitting used in open spaces to lighten: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and mounting: post-top mounting. Mounting grip integrated with the fitting.


# MITRA LED BASIC 3850LM 4000K MAT IP66 I KL. (45W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	957116	Dimensions (H/W/T/S) [mm]:	398/398/174
EAN:	5905963957116	Ingress protection:	IP66
Light source:	LED module	Mounting version:	top
Nominal power [W]:	37	Working temperature [°C]:	from -40 to +35
Rated power of the luminaire [W]:	45	Wire type:	H07RN-F
Luminous flux [lm]:	3850	Number on the palette [pcs]:	48
Luminous efficacy [lm/W]:	87	Net weight [kg]:	1.900
Energy efficiency class:	F	Warranty [years]:	5
Electrical protection class:	I	Category type:	Park and city lighting
Colour temperature [K]:	4000	Category of application:	parkings and bicycle paths
Colour rendering index:	80	LED lifespan L70B50 [h]:	120000
SDCM:	≤ 5	ULOR:	0%
Surge protection [kV]:	2	Warranty [years]:	5
Diffuser material:	PC	Manual:	<a href="#">Download PDF</a>
Diffuser type:	matt	CE certificate:	<a href="#">101/2023</a>
Material of the body:	PP+FG	Plik LDT:	<a href="#">Download</a>
Colour of the body:	grey		

## LIGHT CURVES



# MITRA LED BASIC 3850LM 4000K MAT IP66 I KL. (45W)

DETAILED CARD

## TECHNICAL DETAILS



MITRA LED



MITRA LED

Card creation date: 04 June 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 101/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)