

# DIONE LED PLUS 2700LM 830 IP65 I KL. OPAL WHITE 25W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	943379
<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	25
<b>Luminous flux [lm]*:</b>	2700
<b>Colour temperature [K]:</b>	3000
<b>SDCM:</b>	3
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	ABS
<b>Ring material:</b>	ABS

## CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy-saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows keeping the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency, and optimal use of electricity (Power Factor).

The fitting is offered in RCR version:

- sensor used to detect motion; for detection uses microwaves (active sensor).

## APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

# DIONE LED PLUS 2700LM 830 IP65 I KL. OPAL WHITE 25W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	943379	Impact resistance:	IK10
Light source:	LED module	Ingress protection:	IP65
Nominal power [W]:	25	Mounting version:	surface
Rated power of the luminaire [W]:	26	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Dimensions of single box [mm]:	340/340/115
Frequency [Hz]:	50 - 60	Net weight [kg]:	1
Luminous flux [lm]:	2700	Permeability factor of the diffuser:	0.73
Luminous efficacy [lm/W]:	94	Category type:	bulkheads
Energy efficiency class:	E	AC voltage range [V]:	198-264
Electrical protection class:	I	DC voltage range [V]:	176-280
Colour temperature [K]:	3000	LED lifespan L70B50 [h]:	130000
Color rendering index (Ra) >:	80	LED lifespan L80B10 [h]:	80000
SDCM:	3	LED lifespan L90B10 [h]:	35000
Power factor:	0.95	Light distribution type:	open space
Beam angle [°]:	120	Surge protection [kV]:	1
Diffuser material:	PC	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser type:	OPAL	Warranty [years]:	5
Diffuser colour:	white	CE certificate:	<a href="#">378/2023</a>
Material of the body:	ABS	ENEC Certificate:	<a href="#">PL BBJ/011/2021/M1/A1</a>
Colour of the body:	white	Environmental Product Declaration (EPD):	944/2026
Ring material:	ABS	Manual:	<a href="#">Download PDF</a>
Ring colour:	white	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Dimensions (H/W/T/S) [mm]:	ø340/115	Plik LDT:	<a href="#">Download</a>
Mounting dimensions [mm]:	140		

# DIONE LED PLUS 2700LM 830 IP65 I KL. OPAL WHITE 25W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant (120DL118)

Card creation date: 07 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 378/2023