

DIONE LED PLUS 2900LM 840 IP65 I KL. DALI OPAL WHITE 25W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	943423
Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W]:	25
Luminous flux [lm]*:	2900
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy-saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows keeping the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency, and optimal use of electricity (Power Factor).

The fitting is offered in RCR version:

- sensor used to detect motion; for detection uses microwaves (active sensor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS 2900LM 840 IP65 I KL. DALI OPAL WHITE 25W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ingress protection:	IP65
Nominal power [W]:	25	Mounting version:	surface
Rated power of the luminaire [W]:	26	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	DIMM DALI:	yes
Frequency [Hz]:	50 - 60	Dimensions of single box [mm]:	340/340/115
Luminous flux [lm]:	2900	Net weight [kg]:	1
Luminous efficacy [lm/W]:	102	Warranty [years]:	5
Energy efficiency class:	E	Permeability factor of the diffuser:	0.73
Electrical protection class:	I	Index:	943423
Colour temperature [K]:	4000	Category type:	bulkheads
Colour rendering index:	80	AC voltage range [V]:	198-264
SDCM:	≤ 3	DC voltage range [V]:	176-280
Power factor:	0.92	LED lifespan L70B50 [h]:	130000
Beam angle [°]:	120	LED lifespan L80B20 [h]:	80000
Diffuser material:	PC	LED lifespan L90B10 [h]:	35000
Diffuser type:	OPAL	Light distribution type:	open space
Diffuser colour:	white	CE certificate:	378/2023
Material of the body:	ABS	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	white	Surge protection [kV]:	1
Ring material:	ABS	Manual:	Download PDF
Ring colour:	white	PZH certificate:	B-BK-60212-0619/20
Dimensions (H/W/T/S) [mm]:	ø340/115	ENEC Certificate:	PL BBJ/011/2021/M1/A1
Mounting dimensions [mm]:	140	Plik LDT:	Download
Impact resistance:	IK10		

DIONE LED PLUS 2900LM 840 IP65 I KL. DALI OPAL WHITE 25W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white
matt RAL 9003 painted vandal
resistant (120DL118)

Card creation date: 30 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 378/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl