

DIONE LED PLUS 2900LM 840 IP65 I KL. DALI RCR OPAL WHITE 25W CORRIDOR

DETAILED CARD



TECHNICAL PARAMETERS

Index:	943447
Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W]:	25
Luminous flux [lm]*:	2900
Colour temperature [K]:	4000
SDCM:	3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy-saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows keeping the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency, and optimal use of electricity (Power Factor).

The fitting is offered in RCR version:

- sensor used to detect motion; for detection uses microwaves (active sensor).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS 2900LM 840 IP65 I KL. DALI RCR OPAL WHITE 25W CORRIDOR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	943447	Ingress protection:	IP65
Light source:	LED module	Mounting version:	surface
Nominal power [W]:	25	Working temperature [°C]:	from -20 to +35
Rated power of the luminaire [W]:	26	Corridor function:	yes
Supply voltage [V]:	220-240	Motion sensor:	yes
Frequency [Hz]:	50 - 60	DIMM DALI:	yes
Luminous flux [lm]:	2900	Dimensions of single box [mm]:	340/340/115
Luminous efficacy [lm/W]:	102	Net weight [kg]:	1
Energy efficiency class:	E	Permeability factor of the diffuser:	0.73
Electrical protection class:	I	Category type:	bulkheads
Colour temperature [K]:	4000	AC voltage range [V]:	198-264
Color rendering index (Ra) >:	80	DC voltage range [V]:	176-280
SDCM:	3	LED lifespan L70B50 [h]:	130000
Power factor:	0.92	LED lifespan L80B10 [h]:	80000
Max load (RCR) [W]:	400	LED lifespan L90B10 [h]:	35000
Beam angle [°]:	120	Light distribution type:	open space
Diffuser material:	PC	Surge protection [kV]:	1
Diffuser type:	OPAL	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser colour:	white	Warranty [years]:	5
Material of the body:	ABS	CE certificate:	378/2023
Colour of the body:	white	ENEC Certificate:	PL BBJ/011/2021/M1/A1
Ring material:	ABS	Environmental Product Declaration (EPD):	944/2026
Ring colour:	white	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	ø340/115	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Mounting dimensions [mm]:	140	Pliik LDT:	Download
Impact resistance:	IK10		

DIONE LED PLUS 2900LM 840 IP65 I KL. DALI RCR OPAL WHITE 25W CORRIDOR

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant (120DL118)

Card creation date: 07 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 378/2023