

# SQ 300 LED PLUS LENS 2100LM 830 IP54 II KL. DALI RCR OPAL RAL9005 (24W) 300MM CORRIDOR

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	664342
Ingress protection:	IP54
Impact resistance:	IK08
Nominal power [W]:	24
Luminous flux [lm]*:	2100
Colour temperature [K]:	3000
Energy efficiency class:	F
Material of the body:	ABS
Diffuser material:	PS
Diffuser type:	OPAL

## CHARACTERISTICS

SQ 300 LED is a new line of square ceiling lamps. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, thanks to which it is characterized by low weight and high impact resistance (IK08). The diffuser made of PC polycarbonate provides the lamp with excellent lighting properties. Integrated LED module provides low power consumption and all the advantages of modern lamps with an LED source. The PLUS version of the luminaire line is equipped with brand components from recognized global manufacturers. It is characterized by extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

## APPLICATION

The surface-mounted lamp for ceiling or wall mounting is intended for both indoor use - in rooms with high humidity, passageways, staircases, and outdoor use as façade lighting.


# SQ 300 LED PLUS LENS 2100LM 830 IP54 II KL. DALI RCR OPAL RAL9005 (24W) 300MM CORRIDOR

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	664342	Dimensions of single box [mm]:	305x305x60
Light source:	LED module	Net weight [kg]:	1
Nominal power [W]:	24	Warranty [years]:	5
Rated power of the luminaire [W]:	27	Category type:	bulkheads
Supply voltage [V]:	220 - 240	Category of application:	HoReCa, commercial facilities, educational institutions
Frequency [Hz]:	50 - 60	AC voltage range [V]:	198 -264
Luminous flux [lm]:	2100	LED lifespan L70B50 [h]:	120000
Luminous efficacy [lm/W]:	85	LED lifespan L80B20 [h]:	80000
Energy efficiency class:	F	LED lifespan L90B10 [h]:	40000
Electrical protection class:	II	Light distribution type:	open space
Colour temperature [K]:	3000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Beam angle [°]:	120	SDCM:	≤ 3
Diffuser material:	PS	Power factor:	0.92
Diffuser type:	OPAL	Max load (RCR) [W]:	400
Diffuser colour:	white	Surge protection [kV]:	1
Optics material:	PMMA	Working temperature [°C]:	from -20 to +35
Optics:	lens	Corridor function:	yes
Material of the body:	ABS	Permeability factor of the diffuser:	0.70
Colour of the body:	black	DC voltage range [V]:	176 - 280
Dimensions (H/W/T/S) [mm]:	300/300/58	Version:	LENS
Mounting dimensions [mm]:	210	Warranty [years]:	5
Impact resistance:	IK08	CE certificate:	<a href="#">111/2023</a>
Ingress protection:	IP54	PZH certificate:	<a href="#">B-BK-60212-0479/21</a>
Mounting version:	surface	Manual:	<a href="#">Download PDF</a>
Motion sensor:	yes	ENEC Certificate:	<a href="#">0316/ENEC/23</a>
DIMM DALI:	yes		

## LIGHT CURVES



Card creation date: 26 January 2024  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 111/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)