

TYTAN 2 LED ENDURA PLUS 1450MM 5950LM 840 IP66 35W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|--------|
| Index: | 909849 |
| Ingress protection: | IP66 |
| Impact resistance: | IK09 |
| Nominal power [W]: | 35 |
| Luminous flux [lm]*: | 5950 |
| Colour temperature [K]: | 4000 |
| Energy efficiency class: | C |
| Material of the body: | PC |
| Colour of the body: | grey |
| Diffuser material: | PC |

CHARACTERISTICS

TYTAN 2 LED ENDURA is a fitting from NEXT GEN line, which is a new generation of fittings in LED technology. The fitting, designed from scratch, allows new solutions improving the light distribution and temperature balance. Branded led diodes and new LED modules have influence on a very high luminous flux: 155 lm/W. It guarantees the best required lighting level and energy saving up to 68%. The solution based on integration of the diffuser and LED modul is applied in the fitting. The fitting has a lot of facilities making the mounting easier and faster: the system of diffuser suspension, adjustable mounting brackets ensuring the mounting tolerance +/-50mm. Standard equipment of the fitting: clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation.

APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.

TYTAN 2 LED ENDURA PLUS 1450MM 5950LM 840 IP66 35W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|-----------------|--------------------------|--|
| Nominal power [W]: | 35 | Ingress protection: | IP66 |
| Index: | 909849 | Mounting version: | surface, suspended |
| Light source: | LED module | Net weight [kg]: | 1.800 |
| Colour temperature [K]: | 4000 | Mark D: | yes |
| Luminous flux [lm]: | 5950 | PKP Certificate: | 1 |
| Rated power of the luminaire [W]: | 38.90 | Category type: | battens |
| Diffuser type: | MAT | Category of application: | industrial |
| Supply voltage [V]: | 220-240 | AC voltage range [V]: | 198- 264 |
| Frequency [Hz]: | 50 - 60 | DC voltage range [V]: | 170 - 280 |
| Working temperature [°C]: | from -40 to +60 | LED lifespan L70B50 [h]: | 91000 |
| Luminous efficacy [lm/W]: | 153 | LED lifespan L80B20 [h]: | 57000 |
| Dimensions (H/W/T/S) [mm]: | 1432/85/80 | LED lifespan L90B10 [h]: | 28000 |
| Energy efficiency class: | C | Photobiological safety: | RG0 - exempt (no photobiological hazard) |
| Electrical protection class: | I | Version: | PLUS |
| Colour rendering index: | >80 | Warranty [years]: | 5 |
| SDCM: | ≤ 3 | Warranty [years]: | 5 |
| Power factor: | 0.94 | CE certificate: | 131/2023 |
| Diffuser material: | PC | PZH certificate: | B-BK-60212-0152/20 |
| Material of the body: | PC | HACCP: | 852/2004 |
| Colour of the body: | grey | ENEC Certificate: | 0310/ENEC/23 |
| Impact resistance: | IK09 | Manual: | Download PDF |
| | | Plik LDT: | |

TECHNICAL DETAILS



regulowane uchwyty / adjustable handles / einstellbare Halterungen



system zwieszania klosza / suspension system of the diffuser / hängende Diffusor



wybór miejsca zasilania / choosing a place of power supply / Stromversorgungsanschluss von mehreren Seite möglich

TYTAN 2 LED ENDURA PLUS 1450MM 5950LM 840 IP66 35W

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|----------|---|
| 908200 | TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) |
| 60000006 | M16 stuffing box plug various PA black M-16 - BPM-21 |
| 80000279 | Gland. beam, Codar, soft polyvinyl chloride (PVC-P), gray |



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 131/2023