

# TYTAN 2 LED ENDURA MINUS 1150MM 9050LM 840 IP66 LS2 55W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	911514
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK09
<b>Nominal power [W]:</b>	55
<b>Luminous flux [lm]*:</b>	9050
<b>Colour temperature [K]:</b>	4000
<b>Energy efficiency class:</b>	C
<b>Material of the body:</b>	PC
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

TYTAN 2 LED ENDURA is a fitting from NEXT GEN line, which is a new generation of fittings in LED technology. The fitting, designed from scratch, allows new solutions improving the light distribution and temperature balance. Branded led diodes and new LED modules have influence on a very high luminous flux: 155 lm/W. It guarantees the best required lighting level and energy saving up to 68%. The solution based on integration of the diffuser and LED modul is applied in the fitting. The fitting has a lot of facilities making the mounting easier and faster: the system of diffuser suspension, adjustable mounting brackets ensuring the mounting tolerance +/-50mm. Standard equipment of the fitting: clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation.

## APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.


# TYTAN 2 LED ENDURA MINUS 1150MM 9050LM 840 IP66 LS2 55W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	911514	Mounting version:	surface, suspended
Light source:	LED module	Working temperature [°C]:	from -40 to +45
Nominal power [W]:	55	Wire type:	5x1,5
Rated power of the luminaire [W]:	59.30	Through wiring:	LS2
Supply voltage [V]:	220 - 240	Net weight [kg]:	1
Frequency [Hz]:	50 - 60	Category type:	battens
Luminous flux [lm]:	9050	Category of application:	industrial
Luminous efficacy [lm/W]:	153	LED lifespan L70B50 [h]:	85000
Energy efficiency class:	C	LED lifespan L80B20 [h]:	54000
Electrical protection class:	I	LED lifespan L90B10 [h]:	26000
Colour temperature [K]:	4000	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Colour rendering index:	>80	Exchangeable source:	yes
SDCM:	≤ 3	Surge protection [kV]:	4
Power factor:	0.95	Mounting dimensions [mm]:	800
Diffuser material:	PC	Version:	MINUS
Diffuser type:	MAT	Warranty [years]:	5
Material of the body:	PC	CE certificate:	<a href="#">130/2023</a>
Colour of the body:	grey	PZH certificate:	<a href="#">B-BK-60212-0152/20</a>
Dimensions (H/W/T/S) [mm]:	1152/85/80	HACCP:	<a href="#">852/2004</a>
Impact resistance:	IK09	ENEC Certificate:	<a href="#">0310/ENEC/23</a>
Ingress protection:	IP66	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES



# TYTAN 2 LED ENDURA MINUS 1150MM 9050LM 840 IP66 LS2 55W

DETAILED CARD

## TECHNICAL DETAILS



regulowane uchwyty / adjustable  
handles / einstellbare Halterungen



system zwieszania klosza / suspension  
system of the diffuser / hängende  
Diffusor



wybór miejsca zasilania / choosing a  
place of power supply /  
Stromversorgungsanschluss von  
mehreren Seite möglich

# TYTAN 2 LED ENDURA MINUS 1150MM 9050LM 840 IP66 LS2 55W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
60000006	M16 stuffing box plug various PA black M-16 - BPM-21
80000279	Gland. beam, Codar, soft polyvinyl chloride (PVC-P), gray



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 19 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 130/2023