

SWING LED EVO 1950LM 840 25ST. PRM (21W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	094637
Ingress protection:	IP40/20
Nominal power [W]:	21
Luminous flux [lm]*:	1950
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	F
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC

CHARACTERISTICS

Recessed frameless downlight fitting equipped with modern and energy-saving light source LED. The body made of plastic, steel and aluminium ensures a long-term operation of the fitting. The diffuser made of highly transparent PC guarantees high luminous flux and ensures optimal conditions for the LED operation. Due to the possibility of adjusting the light direction vertically up to 30° and horizontally (turn) up to 355°, four options of diffuser to choose: 60°, 25°, 59°/92°, as well as modern and elegant design, the fitting is suitable for a variety of applications.

APPLICATION

Recessed fitting suitable for mounting in plasterboard ceilings, dedicated for indoor use as a basic or accent lighting. Due to modern and elegant design and the possibility of choosing the optimal light distribution, the fitting is ideal for offices, commercial buildings and passageways.

SWING LED EVO 1950LM 840 25ST. PRM (21W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	21	Mounting dimensions [mm]:	ø196
Index:	094637	Ingress protection:	IP40/20
Colour temperature [K]:	4000	Glow wire test [°C]:	650
Light source:	LED module	Mounting version:	recessed
Luminous flux [lm]:	1950	Working temperature [°C]:	from -20 to +35
Beam angle [°]:	25	Tilt angle adjustment [°]:	30/355
Rated power of the luminaire [W]:	23	Net weight [kg]:	1.200
Energy efficiency class:	F	Warranty [years]:	5
Supply voltage [V]:	220-240	Category type:	downlights
Frequency [Hz]:	50 - 60	Category of application:	architectural, commercial facilities, educational institutions
Luminous efficacy [lm/W]:	92	AC voltage range [V]:	198-264
Electrical protection class:	I	LED lifespan L70B50 [h]:	90000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	86000
SDCM:	≤ 3	LED lifespan L90B10 [h]:	45000
Power factor:	0.91	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Surge protection [kV]:	2	Warranty [years]:	5
Diffuser material:	PC	Manual:	Download PDF
Material of the body:	ABS	CE certificate:	351/2023
Colour of the body:	white	Plik LDT:	Pobierz
Dimensions (H/W/T/S) [mm]:	ø178/163		

Card creation date: 23 September 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 351/2023