

SQ 160 LED N 2100LM PRM 830 (17W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	571138
Ingress protection:	IP33
Nominal power [W]:	17
Luminous flux [lm]*:	2100
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	D
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PS

CHARACTERISTICS

SQ 160 LED N is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.


SQ 160 LED N 2100LM PRM 830 (17W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	17	Dimensions (H/W/T/S) [mm]:	162/162/86
Index:	571138	Mounting dimensions [mm]:	113
Colour temperature [K]:	3000	Impact resistance:	IK08
Light source:	LED module	Ingress protection:	IP33
Luminous flux [lm]:	2100	Glow wire test [°C]:	650
Diffuser type:	PRM	Mounting version:	surface
Rated power of the luminaire [W]:	18	Working temperature [°C]:	from -20 to +35
Beam angle [°]:	115	Net weight [kg]:	0.400
Supply voltage [V]:	220 - 240	Warranty [years]:	5
Energy efficiency class:	D	Category type:	downlights
Frequency [Hz]:	50 - 60	LED lifespan L70B50 [h]:	132000
Luminous efficacy [lm/W]:	111	LED lifespan L80B20 [h]:	84000
Electrical protection class:	I	LED lifespan L90B10 [h]:	42000
Colour rendering index:	>80	Photobiological safety:	RG0 - exempt (no photobiological hazard)
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.99	Category of application:	HoReCa, commercial facilities, educational institutions, art and culture
Diffuser material:	PS	Manual:	Download PDF
Material of the body:	ABS	CE certificate:	314/2023
Colour of the body:	white	Plik LDT:	Download

LIGHT CURVES



SQ 160 LED N 2100LM PRM 830 (17W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
573743	Suspension SQ160 157x157mm black ON/OFF. DALI

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 314/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl