RQ 160 LED P 1900LM 75DEG 830 (17W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	570285
Ingress protection:	IP44/20
Nominal power [W]:	17
Luminous flux [lm]*:	1900
Colour temperature [K]:	3000
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC

CHARACTERISTICS

RQ 160 LED P is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

RQ 160 LED P 1900LM 75DEG 830 (17W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	570285
Light source:	LED module
Nominal power [W]:	17
Rated power of the luminaire [W]:	18
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	1900
Luminous efficacy [lm/W]:	101
Energy efficiency class:	E
Electrical protection class:	I
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.99
Beam angle [°]:	75
Diffuser material:	PC
Diffuser type:	OPAL
Optics:	lens
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	162/70

Mounting dimensions [mm]:	150
Impact resistance:	IK08
Ingress protection:	IP44/20
Glow wire test [°C]:	650
Mounting version:	recessed
Working temperature [°C]:	from -20 to +35
Number on the palette [pcs]:	420
Warranty [years]:	5
Luminous flux of the luminaire 0 min [lm]*:	1922
ITHD [%]:	16
LED lifespan L70B50 [h]:	150000
LED lifespan L80B10 [h]:	100000
LED lifespan L90B10 [h]:	50000
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	5
Category of application:	educational institutions, HoReCa, commercial facilities
Manual:	Download PDF
CE certificate:	318/2023
PZH certificate:	B-BK-60112-0365/2022
ISO Certificates:	9001:2015. 14001:2015. 45001:2018. 50001:2018
Plik LDT:	Download

LIGHT CURVES




RQ 160 LED P 1900LM 75DEG 830 (17W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
897269	Cover frame for RQ160 D205mm white RAL 9003



Cover frame for RQ160 D205mm white RAL 9003 (897269)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 318/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl