

# RQ 160 LED P 2450LM MAT 840 (21W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                                     |         |
|-------------------------------------|---------|
| <b>Index:</b>                       | 570049  |
| <b>Ingress protection:</b>          | IP44/20 |
| <b>Nominal power [W]:</b>           | 21      |
| <b>Luminous flux [lm]*:</b>         | 2450    |
| <b>Colour temperature [K]:</b>      | 4000    |
| <b>Electrical protection class:</b> | I       |
| <b>Energy efficiency class:</b>     | E       |
| <b>Material of the body:</b>        | ABS     |
| <b>Colour of the body:</b>          | white   |
| <b>Diffuser material:</b>           | PC      |

## CHARACTERISTICS

RQ 160 LED P is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

## APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.


# RQ 160 LED P 2450LM MAT 840 (21W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |            |   |   |
|-----------------------------------|------------|---|---|
| Index:                            | 570049     | Ingress protection:                         | IP44/20   |
| Light source:                     | LED module | Glow wire test [°C]:                        | 650   |
| Nominal power [W]:                | 21         | Mounting version:                           | recessed  |
| Rated power of the luminaire [W]: | 22         | Working temperature [°C]:                   | from -20 to +35   |
| Supply voltage [V]:               | 220 - 240  | Number on the palette [pcs]:                | 420   |
| Frequency [Hz]:                   | 50 - 60    | Warranty [years]:                           | 5   |
| Luminous flux [lm]:               | 2450       | Flicker procent:                            | 67  |
| Luminous efficacy [lm/W]:         | 111        | Luminous flux of the luminaire 0 min [lm]*: | 2450  |
| Energy efficiency class:          | E          | ITHD [%]:                                   | 16  |
| Electrical protection class:      | I          | LED lifespan L70B50 [h]:                    | 132000  |
| Colour temperature [K]:           | 4000       | LED lifespan L80B10 [h]:                    | 84000   |
| Color rendering index (Ra) >:     | 80         | LED lifespan L90B10 [h]:                    | 42000   |
| SDCM:                             | 3          | Photobiological safety:                     | RG0 - exempt (no photobiological hazard)                |
| Power factor:                     | 0.99       | Warranty [years]:                           | 5   |
| Beam angle [°]:                   | 110        | Category of application:                    | educational institutions, HoReCa, commercial facilities |
| Diffuser material:                | PC         | Manual:                                     | <a href="#">Download PDF</a>                            |
| Diffuser type:                    | mat        | CE certificate:                             | <a href="#">318/2023</a>                                |
| Material of the body:             | ABS        | ETIM class:                                 | EC002892  |
| Colour of the body:               | white      | PZH certificate:                            | <a href="#">B-BK-60112-0365/2022</a>                    |
| Dimensions (H/W/T/S) [mm]:        | 162/70     | ISO Certificates:                           | 9001:2015. 14001:2015. 45001:2018. 50001:2018           |
| Mounting dimensions [mm]:         | 150        | Plik LDT:                                   | <a href="#">Download</a>                                |
| Impact resistance:                | IK08       |   |   |

## LIGHT CURVES



# RQ 160 LED P 2450LM MAT 840 (21W)

DETAILED CARD

## ACCESSORIES AVAILABLE

| index  | Name  |
|--------|---|
| 897269 | Cover frame for RQ160 D205mm white RAL 9003 |



Cover frame for RQ160 D205mm white  
RAL 9003 (897269)

Card creation date: 10 February 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 318/2023