MAGNUM HOBBY 50W I KL. OCHR. Z GNIAZDEM PL-FR

DETAILED CARD





TECHNICAL PARAMETERS

Index:	406478
Ingress protection:	IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	50
Colour temperature [K]:	4000
Luminous flux [lm]*:	5500
Supply voltage [V]:	220-240
Electrical protection class:	1
Material of the body:	PP
Colour of the body:	green

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The family of durable and handy luminaires has been designed to illuminate larger areas.



MAGNUM HOBBY 50W I KL. OCHR. Z GNIAZDEM PL-FR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Rated power of the luminaire [W]:	50
Colour temperature [K]:	4000
Luminous flux [lm]:	5500
Diffuser type:	frozen
Plug type:	UNI-SCHUKO
Supply voltage [V]:	220-240
Socket type:	PL-FR
Electrical protection class:	1
Sockets:	1
Beam angle [°]:	120
Cable length [m]:	3
Diffuser material:	PC
Material of the body:	PP
Colour of the body:	green

Ingress protection:	IP54
Dimensions (H/W/T/S) [mm]:	300/480/75
Impact resistance:	IK10
Net weight [kg]:	3
Warranty [years]:	2
Index:	406478
Category type:	workplace floodlights
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L70B50 [h]:	42000
LED lifespan L80B20 [h]:	85000
LED lifespan L90B10 [h]:	140000
Working temperature [°C]:	from -20 to +35
Wire type:	H07RN-F 3×1,5mm
Manual:	Download PDF

Card creation date: 17 September 2020



